



Holzbauschrauben OK Line Speed - Technische Daten

Ausführung mit Reibspitze




Art.-Nr.	Antrieb	Ø d1	Länge L	Gewindelänge L1	Kopf Ø d2	Kopfhöhe k	Kopfhöhe t	Länge Reibspitze lb	Länge Reibspitze lb
85.162.4040	TX 25	4.0 mm	40 mm	25 mm	8 mm	4.4 mm	1.8 mm	12.3 mm	12.3 mm
85.162.4050	TX 25	4.0 mm	50 mm	30 mm	8 mm	4.4 mm	1.8 mm	12.3 mm	12.3 mm
85.162.4060	TX 25	4.0 mm	60 mm	35 mm	8 mm	4.4 mm	1.8 mm	12.3 mm	12.3 mm
85.162.4070	TX 25	4.0 mm	70 mm	40 mm	8 mm	4.4 mm	1.8 mm	12.3 mm	12.3 mm
85.162.4550	TX 25	4.5 mm	50 mm	30 mm	9 mm	4.7 mm	2.1 mm	13.65 mm	13.65 mm
85.162.4560	TX 25	4.5 mm	60 mm	35 mm	9 mm	4.7 mm	2.1 mm	13.65 mm	13.65 mm
85.162.4570	TX 25	4.5 mm	70 mm	40 mm	9 mm	4.7 mm	2.1 mm	13.65 mm	13.65 mm
85.162.4580	TX 25	4.5 mm	80 mm	50 mm	9 mm	4.7 mm	2.1 mm	13.65 mm	13.65 mm
85.162.5040	TX 25	5.0 mm	40 mm	25 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.5045	TX 25	5.0 mm	45 mm	25 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.5050	TX 25	5.0 mm	50 mm	35 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.5060	TX 25	5.0 mm	60 mm	35 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.5070	TX 25	5.0 mm	70 mm	40 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.5080	TX 25	5.0 mm	80 mm	50 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.5090	TX 25	5.0 mm	90 mm	55 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.50100	TX 25	5.0 mm	100 mm	60 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.50120	TX 25	5.0 mm	120 mm	70 mm	10 mm	5.3 mm	2.1 mm	14.1 mm	14.1 mm
85.162.6050	TX 40	6.0 mm	50 mm	35 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	18 mm
85.162.6060	TX 40	6.0 mm	60 mm	35 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	18 mm
85.162.6070	TX 40	6.0 mm	70 mm	40 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	18 mm

mit Reibeteil und Reibspitze



Art.-Nr.	Antrieb	Ø d1	Länge L	Gewindelänge L1	Kopf Ø d2	Kopfhöhe k	Kopfhöhe t	Länge Reibspitze lb	Länge Reibteil LR
85.162.6080	TX 40	6.0 mm	80 mm	50 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.6090	TX 40	6.0 mm	90 mm	50 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60100	TX 40	6.0 mm	100 mm	50 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60120	TX 40	6.0 mm	120 mm	50 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60140	TX 40	6.0 mm	140 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60160	TX 40	6.0 mm	160 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60180	TX 40	6.0 mm	180 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60200	TX 40	6.0 mm	200 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60220	TX 40	6.0 mm	220 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60240	TX 40	6.0 mm	240 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60260	TX 40	6.0 mm	260 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60280	TX 40	6.0 mm	280 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm
85.162.60300	TX 40	6.0 mm	300 mm	75 mm	13.2 mm	6.9 mm	3.2 mm	18 mm	12 mm



Art.-Nr.	Antrieb	Ø		Länge L	Gewindelänge		Kopfhöhe		Länge Reibspitze		Länge Reibteil	
		d1	d2		L1	L1	k	t	lb	LR		
85.162.8080	TX 40	8.0 mm	15 mm	80 mm	50 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80100	TX 40	8.0 mm	15 mm	100 mm	50 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80120	TX 40	8.0 mm	15 mm	120 mm	80 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80140	TX 40	8.0 mm	15 mm	140 mm	80 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80160	TX 40	8.0 mm	15 mm	160 mm	80 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80180	TX 40	8.0 mm	15 mm	180 mm	80 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80200	TX 40	8.0 mm	15 mm	200 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80220	TX 40	8.0 mm	15 mm	220 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80240	TX 40	8.0 mm	15 mm	240 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80260	TX 40	8.0 mm	15 mm	260 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80280	TX 40	8.0 mm	15 mm	280 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80300	TX 40	8.0 mm	15 mm	300 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80320	TX 40	8.0 mm	15 mm	320 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80340	TX 40	8.0 mm	15 mm	340 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80360	TX 40	8.0 mm	15 mm	360 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80380	TX 40	8.0 mm	15 mm	380 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80400	TX 40	8.0 mm	15 mm	400 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80450	TX 40	8.0 mm	15 mm	450 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80500	TX 40	8.0 mm	15 mm	500 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80550	TX 40	8.0 mm	15 mm	550 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.80600	TX 40	8.0 mm	15 mm	600 mm	100 mm	100 mm	7.25 mm	3.9 mm	22.9 mm	12 mm		
85.162.1080	TX 50	10.0 mm	19 mm	80 mm	50 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10100	TX 50	10.0 mm	19 mm	100 mm	50 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10120	TX 50	10.0 mm	19 mm	120 mm	80 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10140	TX 50	10.0 mm	19 mm	140 mm	80 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10160	TX 50	10.0 mm	19 mm	160 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10180	TX 50	10.0 mm	19 mm	180 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10200	TX 50	10.0 mm	19 mm	200 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10220	TX 50	10.0 mm	19 mm	220 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10240	TX 50	10.0 mm	19 mm	240 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10260	TX 50	10.0 mm	19 mm	260 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10280	TX 50	10.0 mm	19 mm	280 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10300	TX 50	10.0 mm	19 mm	300 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10320	TX 50	10.0 mm	19 mm	320 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10340	TX 50	10.0 mm	19 mm	340 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10360	TX 50	10.0 mm	19 mm	360 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10380	TX 50	10.0 mm	19 mm	380 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		
85.162.10400	TX 50	10.0 mm	19 mm	400 mm	100 mm	100 mm	8.7 mm	4.1 mm	24.6 mm	12 mm		